RICHARD LE DROFF

2020 - 2021

Richard Le Droff Product Range 2020/2021

Airtight pellet stove



E MAGIC 7 Verre

ARCHI CERAM Fireplaces

TRI-VISION



300



302



303



500



502



503

BI-VISION



520



522



530



533

ARCHI Airtight Fireplaces

FRONT VIEW



66/50



88/50



88/66



110/50

BI-VISION



65/51

81/51

TRI-VISION



65/52

80/52

50/52/70

TUNNEL



88/50

E MAGIC 7 VERRE

Airtight Pellet Stove




E MAGIC 7 VERRE

Airtight Pellet Stove



Why ?

- Becomes a real design item when there is no fire
- Full glass door
- Ventilation (summer)





- 8 to 18 hours autonomy
- Tank capacity : 19 kg
- Power modulation : 3,5 to 7,5 kW
- Efficiency : 89 %
- Technologies :
    - AGS Technology (Safe and Guaranteed Fire lighting)
    - E-Control (easy installation and after-sales service, integrated control panel)
    - Optima Control
    - E-Service
- Suitable for well-insulated houses
- Connectable pellet stove

ARCHI CERAM

Fireplaces



Monochrome or two-colour style, the choice is yours.

The Archi Ceram covering is made of ceramic because of its great assets :

- Stores heat
- Waterproof
- 100% natural
- Recyclable
- Resistant to extreme temperatures
- Hygienic
- Resistant to UV
- Easy to clean
- Resistant to bending
- Resistant to acids
- Antibacterial



Smart and easy installation

ARCHI CERAM

Fireplaces

Options




❷ Change the colour of the door module

The door module is usually the same colour as the upper module.


❶ Wider ceramic panel

More customisation possibilities




❸ Extend the bench

The bench can be extended up to 40 cm. Both sides of the bench can be extended on Archi Ceram Tri-vision 500.




❹ Deepen the bench

The bench can be deepened up to 10 cm.



❺ Elevate the upper module

The upper module can be elevated up to 40 cm. The elevation of Archi Ceram 300, 302, 303, 520, 522, 530, 533 upper module is only possible when the walls do not need to be protected.



ARCHI CERAM Tri-vision 300 - 302 - 303

Fireplaces



ARCHI CERAM Tri-vision 300 – 302 – 303

Fireplaces




ARCHI CERAM TRI-VISION 300
Krater




ARCHI CERAM TRI-VISION 302
Beton




ARCHI CERAM TRI-VISION 303
Bianco Polare



ARCHI CERAM TRI-VISION 300
Dimensions (L x H x P) : 62,2 x 169 x 50 cm



ARCHI CERAM TRI-VISION 302
Dimensions (L x H x P) : 105 x 169,6 x 50 cm



ARCHI CERAM TRI-VISION 303
Dimensions (L x H x P) : 105 x 169,6 x 50 cm

Why ?

- Retractable full glass door
- Black vermiculite
- Optimized view of the fire with the low grid
- Can be installed close to the wall
- External air intake

- Suitable for well-insulated houses
- Length of the logs : 33 cm
- Nominal output : 5,7 kW
- Power modulation : 2,9 to 7,4 kW
- Efficiency : 82,1 %
- Smoke flue diameter : 200 mm

ARCHI CERAM Tri-vision 500 - 502 - 503

Fireplaces



ARCHI CERAM Tri-vision 500 - 502 - 503

Fireplaces



ARCHI CERAM TRI-VISION 500
La Bohême




ARCHI CERAM TRI-VISION 502
Krater




ARCHI CERAM TRI-VISION 503
Iron Corten

Why ?


- Retractable full glass door
- Black vermiculite
- Optimized view of the fire with the low grid
- Can be installed close to the wall
- External air intake



ARCHI CERAM TRI-VISION 500
Dimensions (L x H x P) : 120 x 169,8 x 50 cm



ARCHI CERAM TRI-VISION 502
Dimensions (L x H x P) : 120 x 169,8 x 50 cm



ARCHI CERAM TRI-VISION 503
Dimensions (L x H x P) : 120 x 169,8 x 50 cm

- Suitable for well-insulated houses
- Length of the logs : 50 cm
- Nominal output : 7,8 kW
- Power modulation : 3,5 to 10 kW
- Efficiency : 82,9 %
- Smoke flue diameter : 150 mm

ARCHI CERAM Bi-vision 520 - 522 – 530 - 533

Fireplaces



ARCHI CERAM Bi-vision 520 - 522 – 530 - 533

Fireplaces



ARCHI CERAM
BI-VISION 520 droite
white arctic




ARCHI CERAM
BI-VISION 522 droite
Iron grey




ARCHI CERAM
BI-VISION 530 gauche
Nero zimbabwe




ARCHI CERAM
BI-VISION 533 gauche
Beton




ARCHI CERAM
BI-VISION 520
Dimensions (L x H x P) :
81,4 x 170 x 52,5 cm



ARCHI CERAM
BI-VISION 522
Dimensions (L x H x P) :
120 x 170 x 52,5 cm



ARCHI CERAM
BI-VISION 530
Dimensions (L x H x P) :
81,4 x 170 x 52,5 cm



ARCHI CERAM
BI-VISION 533
Dimensions (L x H x P) :
120 x 170 x 52,5 cm

Why ?

- Retractable full glass door
- Black vermiculite
- Optimized view of the fire with the low grid
- Can be installed close to the wall
- External air intake

- Suitable for well-insulated houses
- Length of the logs : 50 cm
- Nominal output : 7,8 kW
- Power modulation : 3,5 to 10 kW
- Efficiency : 82,9 %

ARCHI 66/50

Airtight fireplace



ARCHI 88/50

Airtight fireplace



ARCHI 88/66

Airtight fireplace



ARCHI 110/50

Airtight fireplace




ARCHI 66/50, 88/50, 88/66, 110/50

Airtight fireplaces



ARCHI 66/50


•Nominal output : 7,8 kW
•Power modulation : 3,9 to 10,1 kW
•Efficiency : 85 %
• smoke flue diameter : 200 mm





ARCHI 88/50


•Nominal output : 9 kW
•Power modulation : 4,5 to 11,7 kW
•Efficiency : 81,4 %
•smoke flue diameter : 200 mm





ARCHI 88/66


•Nominal output : 10,9 kW
•Power modulation : 5,5 to 14,2 kW
•Efficiency : 81,2 %
•smoke flue diameter : 200 mm





ARCHI 110/50

•Nominal output : 12 kW
•Power modulation : 6 to 15,6 kW
•Efficiency : 82,7 %
•smoke flue diameter : 200 mm



Why ?

• Retractable full glass door. Quiet system.
• Black vermiculite
• Optimized view of the fire with the low grid
• Easy to install
• Optional frame
• Suitable for well-insulated houses
•Length of the logs : 50 cm
•External air intake



ARCHI BI-VISION 65/51

Airtight fireplace

ARCHI BI-VISION 81/51

Airtight fireplace



ARCHI BI-VISION 65/51 et 81/51

Airtight fireplace




ARCHI BI-VISION 65/51 droit



ARCHI BI-VISION 81/51 droit


•Nominal output : 6,9 kW
•Power modulation : 3,5 to 9 kW
•Efficiency : 84,85 %
• smoke flue diameter : 200 mm

•Nominal output : 12 kW
•Power modulation : 6 to 15,6 kW
•Efficiency : 83,25 %
• smoke flue diameter : 200 mm



ARCHI bi-vision 65/51 droit
Dimensions (L x H x P) : 87,6 x 135,7 x 62,6 cm

ARCHI bi-vision 65/51 gauche
Dimensions (L x H x P) : 87,6 x 135,7 x 62,6 cm



ARCHI bi-vision 81/51 droit
Dimensions (L x H x P) : 103,6 x 135,7 x 62,6 cm

ARCHI bi-vision 81/51 gauche
Dimensions (L x H x P) : 103,6 x 135,7 x 62,6 cm

Why ?

• Retractable full glass door. Quiet system.
• Black vermiculite
• Optimized view of the fire with the low hearth
• Easy to install
• Optional frame
• Suitable for well-insulated houses
•Length of the logs : 50 cm
•External air intake

ARCHI TRI-VISION 65/52

Airtight fireplace



ARCHI TRI-VISION 80/52

Airtight fireplace



ARCHI TRI-VISION 50/52/70

Airtight fireplace



ARCHI TRI-VISION 65/52, 80/52 et 50/52/70

Airtight fireplaces



ARCHI TRI-VISION 65/52

•Nominal output : 7,8 kW
•Power modulation : 3,9 to 10,1 kW
•Efficiency : 82,93 %
• smoke flue diameter : 200 mm



ARCHI TRI-VISION 80/52

•Nominal output : 9,9 kW
•Power modulation : 5 to 12,9 kW
•Efficiency : 80,42 %
• smoke flue diameter : 200 mm




ARCHI TRI-VISION 50/52/70


•Nominal output : 10 kW
•Power modulation : 5 to 13 kW
•Efficiency : 82,7 %
• smoke flue diameter : 200 mm

Why ?


• Retractable full glass door. Quiet system.
• Black vermiculite
• Better view of the fire with the low grid
• Easy to install
• Optional frame
• Suitable for well-insulated houses
•Length of the logs : 50 cm
•External air intake



ARCHI TRI-VISION 65/52
Dimensions (L x H x P) : 80,7 x 134,2 x 56 cm



ARCHI TRI-VISION 80/52
Dimensions (L x H x P) : 95,7 x 134,2 x 56 cm



ARCHI TRI-VISION 50/52/70
Dimensions (L x H x P) : 58,2 x 138,2 x 95 cm

ARCHI TUNNEL 88/50

Airtight fireplace




ARCHI TUNNEL 88/50

Airtight fireplace



Why ?

- Retractable full glass door. Quiet system.
- Black vermiculite
- Optimized view of the fire with the low hearth
- Easy to install
- Optional frame
- Suitable for well-insulated houses
- Length of the logs : 50 cm
- External air intake



ARCHI TUNNEL
Dimensions (L x H x P) : 118,6 x 142,6 x 58,5 cm

- Nominal output : 11,6 kW
- Power modulation : 5,8 to 15,1 kW
- Efficiency : 80,5 %
- smoke flue diameter : 200 mm